

STOCKPORT planter

PRODUCT SPECIFICATION

Technical information							
Material							
Vertical walling slats	95x45mm FSC®-certified treated redwood or FSC®-certified hardwood						
External corner detail (when required)	45x45mm FSC®-certified treated redwood or FSC®-certified hardwood						
Top and Bottom tubular rails	60.3mm Ø x 3mm mild steel or stainless steel CHS						
Internal uprights and cross straps	50x10 and 50x5mm mild steel flat						
Base frame	75x50x3mm RHS, 75x50x6 and 50x50x5mm mild steel angles						
Leg/foot	48.3 Ø x 3mm CHS and 100x100x5mm baseplate						
Base flooring	18mm FSC®-certified hardwood faced plywood						
Fixings	M10 size - bright zinc plated						
Standard finish	Natural						
Optional finish	Stained finish available on request						
Accessories	Integral bench seating Tree Anchor fittings Watering Systems Adjustable feet Trellis panels Pergola structures						
Guarantee	Stockport planters are guaranteed for 15 years						
Walling heights (mm)	460	660	860	1060	1260	1460	
Planting depths (mm)	257	457	657	857	1057	1257	
Weights							
Treated redwood planter walls (kgs / lm)	27	33	41	49	57	65	
Hardwood planter walls (kgs / lm)	37	51	65	79	93	107	
Planter base (kgs / m²)	26	26	26	26	26	26	
Light fill material can be based on:	1000 kgs / m³						
Heavy fill material can be based on:	2000 kgs / m³						

Timber policy

All treated softwood planters are manufactured using materials obtained from growers who operate under the Forest Stewardship Council® (FSC®).

All iroko hardwood planters are manufactured using materials obtained from growers who operate under the Forest Stewardship Council® (FSC®).

Due to continued product improvement, Street Design Limited reserves the right to change the product specification



Street Design

Unit 35 Hayhill Industrial Estate Barrow upon Soar Leicestershire LE12 8LD
01509 815335 sdl@street-design.com www.street-design.com

UK Street Furniture Designers & Manufacturers

Construction

All Street Design products are designed and manufactured using only quality, durable materials, construction details and fixings, to provide a long-lasting, durable life expectancy.

Assembly

Planters up to 2.8 x 2.8m will be delivered to site fully assembled for off loading and positioning on site. Planters larger than 2.8m will be supplied in sections for bolting together on site.

Materials

Hardwood planters are constructed from FSC®-certified hardwood, from sustainable sources. Softwood planters are constructed using FSC®-certified European redwood that has been pressure treated, for a desired service life of 15 years in-ground contact. All mild steel fixings will be M10 size and have a bright zinc plated finish. Planters will be fitted with a geo-textile filter fabric lining, which allows the water to drain through the planter, while retaining the fill material.

Standard finish

FSC treated softwood and iroko hardwood will be left natural to reduce the need for re-staining and help reduce maintenance costs.

Optional finish

Optional stained finish is available on request.

Options

Stockport planters are manufactured to order. Before we can manufacture the planters, we need to know the following:

- Plan size and shapes
- Heights
- Material
- Finish
- Details of accessories required

Accessories

To enhance your Stockport planter and create a product that is suitable for your specific application, you can add from a range of planter accessories.

- Tree anchors
- Adjustable feet
- Watering system
- Integral bench seating
- Pergola structures
- Trellis panels



FSC®-certified natural hardwood rectangular planters in manufacture



FSC®-certified natural hardwood full circular planter with Spalding planter bench



Large FSC®-certified natural treated softwood planters